

## thermio™ eco - thermio™ eco B4B

Item No 04.08.0002.1 / EAN Code 4010940045050



### PRODUCT DESCRIPTION

Push & Forget: Probably the most accurate description of the countdown timer B4B from the thermio™ eco product line. This model offers four boost times for a variety of applications that you can read easily thanks to the large and illuminated LEDs. The Timer switches off automatically and thereby helps you save energy and money.

- ▶ Very easy to operate thanks to an illuminated Boost button – Push, Run & Forget
- ▶ Indication of the system state and remaining system runtime through the system state LEDs
- ▶ Simple, quick and flexible installation thanks to simple electrical connections, external cable feed-through and integrated strain relief

### APPLICATIONS

- ▶ Electric radiators and heating elements
- ▶ Oil fired radiators
- ▶ Electric towel rails
- ▶ Panel heaters
- ▶ Fan heaters
- ▶ Lighting (not discharge lamps)
- ▶ Single immersion heater to 3.000 watts

### TECHNICAL DATA

#### Electrical Data

Supply voltage	AC 230 V ± 10 % 50 Hz
Current output	Switch contact, not potential-free
Current capacity - ohmic load	13 A (3.000 W)
Current capacity - inductive load cos.phi 0.6	5 A / 250 V AC
Load halogen lamp	1.000 W (AC)
Load fluorescent lamps	500 W
Load LED lamp	100 W
Power consumption	1 VA
Accuracy	± 1,5 Second /Day at 20 °C

#### Power connection

Device	Screw terminal with wire protection max. 2.5 mm <sup>2</sup>
--------	--

#### Operating specifications

Operating mode	Boost mode
Manual switch	Boost time
Channels	1

#### Display and format

Shortest switching time	Boost 1, 2, 3, 4 Hours
	ON/OFF 1 Hour
Status indicator	Operation mode Switch position display

#### Operating conditions

Humidity (operating)	20 % ... 60 % relative humidity, non-condensing
Humidity (storage)	20 % ... 60 % relative humidity, non-condensing
Temperature (operation)	±0 °C ... +45 °C
Temperature (storage)	-5 °C ... +55 °C

#### General specifications


Colour	White
Weight	114 g

Material	Thermoplastics, self-extinguishing & high-temperature resistant
Dimension	85 x 85 x 31 mm
Mounting	Flush mounting BS 4662 On-wall BS 5733

Compliance with standards	
Protection type	IP20
Protection class	II, according to corresponding mounting
Approval mark	CE

Scope of delivery	
Housing	strain relief clamps Assembly screws Lustre terminal Screw cover

**DIMENSIONAL DRAWINGS**



**CIRCUIT DIAGRAMS**

