

Hour meters surface mounting - taxxo 100 (UWZ 48 A) Item No 05.15.1001.1 / EAN Code 4010940001339





PRODUCT DESCRIPTION

The taxxo 100 hour meter with AC intended for surface mounting is available in different voltage variants. The device is equipped with a plug base with screw terminals and operates mains synchronised within an ambient temperature of -20 °C ... + 55 °C. The meter can monitor up to 99,999.99 hours of operation. The product complies with the safety guidelines of protection class II and protection type IP20. taxxo is characterised by long-life and maintenance-free technology with robust and reliable design.

Surface mounting for easy and quick installation

APPLICATIONS


- Machinery working time control
- Pumps working time control
- Effective runtime measurement of vehicles and machinery

TECHNICAL DATA

Electrical Data	
Supply voltage	AC 220-240 V ± 10% 50 Hz
Power consumption	1 VA
Accuracy	Mains synchronised
Power connection	
Device	Screw terminal with wire protection max. 2.5 mm ²
	Socket
Display and format	
Meter display	Analogue (7 digits)
	Hours
Operating conditions	
Temperature (operation)	-20 °C +55 °C
General specifications	
Mounting	Surface mounted
	Terminal cover
Compliance with standards	
Protection type	IP20
Protection class	II, according to corresponding mounting
Approval mark	CE, CSA, VDE
Standards and guidelines	EN 60335-1, EN 60335-2-26
Scope of delivery	
Housing	Mounting housing
	Base



DIMENSIONAL DRAWINGS



CIRCUIT DIAGRAMS

