

Hour meters flush mounting - taxxo 112 (UWZ 48 KED)

Item No 05.15.1038.1 / EAN Code 4010940002268



PRODUCT DESCRIPTION

The taxxo 112 hour meters with AC intended for surface mounting is available in different voltage variants. The device is equipped with screw terminals and operates mains synchronised within an ambient temperature of -20 $^{\circ}$ C ... + 55 $^{\circ}$ C. The meter can monitor up to 99,999.99 hours of operation. The product complies with the safety guidelines of protection class II and protection type IP20 and even protection type IP54 by using a baffle with seal. taxxo is characterised by longlife and maintenance-free technology with robust and reliable design.

APPLICATIONS

- ► Machinery working time control
- ► Pumps working time control
- ► Effective runtime measurement of vehicles and machinery







TECHNICAL DATA

Electrical Data		
Supply voltage	AC 220-240 V \pm 10% 50 Hz	
Power consumption	1 VA	
Accuracy	Mains synchronised	

Power connection

Flat connection DIN 6.3 Device

Display and format

Meter display Analogue (7 digits) Hours

Operating conditions

Temperature (operation) -20 °C ... +55 °C

General specifications

Installation Mounting

Compliance with standards


Protection type IP20, IP54 with sealing Protection class II, according to corresponding mounting Approval mark CE, CSA, UL, VDE Standards and guidelines EN 60335-1, EN 60335-2-26


Scope of delivery

Housing Catch frame



DIMENSIONAL DRAWINGS





CIRCUIT DIAGRAMS



