


CU-DIN HVAC KNX

Item number **GTIN**
 EC10430503 4015120430503



Product description

KNX HVAC actuator, 5-channel output switching, 2-channel output, 0–10 V



Technical data

GENERAL

Device category	Actuator
User interface	ETS-Software
Remote controllable	–
Conformity	CE, RoHS, WEEE

ATTACHMENT

Installation type	DIN rail
Installation position	Switching cabinet
Installation dimension	Installation length: 90 mm x Installation width: 72 mm x Installation depth: 65 mm
Type of connection	Push terminal
Connectable wire cross section	0,20 - 6,00 mm ²

HOUSING

Dimensions	Length 90 mm x Width 72 mm x Height/Depth 65 mm
Weight	261 g
Protection type	IP20
Permissible ambient temperature	-5 °C...+45 °C
Relative humidity	5 - 93 %, non-condensing
Colour	grey

ELECTRICAL VERSION

Protection class	II
------------------	----

Nominal voltage	29 - 31 V
Stand-by consumption	< 0.1 W
Power consumption	0,4 W
Power consumption	15 mA

AUTOMATION

Number of inputs	0
Number of analogue outputs	2
Power loss	2 W
Rated current	max. 10 A
Rated current (cos # = 0.8)	max. 10 A
Min. switching capacity	0,1mA / 1V
DC switching capacity (resistive load)	10 A / 12 V DC
Switching capacity incandescent lamps	1600 W
Switching capacity engines	746 W
Switching capacity inductive transformers	1000 W
Switching capacity fluorescent lamps (parallel compensated)	1000 W
Switching capacity fluorescent lamps (uncompensated)	800 W
Rated voltage of analogue outputs	0 - 10 V DC
Nominal current analogue outputs	10 mA
Horizontal pitch (HP)	4

CU-DIN HVAC KNX

Item number **GTIN**
EC10430503 4015120430503

Accessories

Product designation	Item number	GTIN
Temperature sensor for HVAC KNX actuator	EC10430510	4015120430510

Scale drawing

