

DATA SHEET

ALVA BL 940/170 OP 360° 800 830 DALI AN

Item number

EL10820243

GTIN

4015120820243



230 V ~	DALI BUS	DALI	IP65	IK09		CRI >80
LED 3000 K	16 W					

Product description

- LED DALI bollard light made from high-grade aluminium
- Dirt-repellent thanks to powder coating with lotus effect
- Integrated ballast (DALI), installation without further accessories
- High-quality housing, die-cast aluminium, charcoal grey powder-coated, similar to RAL 7024
- Colour temperature 3000 K

Technical data

GENERAL

Device category	Bollard light
User interface	DALI-Bus
Remote controllable	–
Conformity	CE, RoHS, WEEE
Warranty	5 years

ATTACHMENT

Installation type	Free standing
Installation position	Floor
Type of connection	Push terminal
Connectable wire cross section	1,50 - 2,50 mm ²
Number of contacts	5

HOUSING

Dimensions	Height/Depth 940 mm, Ø 170 mm
Weight	7640 g
Material	powder-coated aluminium
Protection type	IP65
Permissible ambient temperature	-25 °C...+40 °C
Relative humidity	5 - 95 %, non-condensing
Impact resistance	IK10
Colour	graphite gray, similar to RAL 7024

ELECTRICAL VERSION

Protection class	I
------------------	---

Nominal voltage	200 - 240 V / 50 - 60 Hz
Power consumption	70 mA
In-rush current	12 A / 57 µs
Leakage current	0,31 mA

LIGHT

Diffusor	opal
Light emission	direct
Beam angle	283 °
Flicker factor	<3 %
Rated output	16 W
Luminous Flux (light)	1030 lm
Luminous efficacy	64 lm/W
Colour temperature	3000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM < 3
Color Quality Scale	80
L70B10 lifetime at 25 °C	105000 h
Life time L70B50 at 25 °C	110000 h
Life time L80B10 at 25 °C	65000 h
Life time L80B50 at 25 °C	70000 h
Life time L90B10 at 25 °C	35000 h
Life time L90B50 at 25 °C	35000 h
Photobiological safety	RG0
Energy efficiency class	A++ to A

DATA SHEET


ALVA BL 940/170 OP 360° 800 830 DALI AN

Item number **GTIN**
EL10820243 4015120820243

Accessories

Product designation	Item number	GTIN
ALVA GROUND ANCHOR	EL10820083	4015120820083

Scale drawing



Light distribution

