

## ELH EL LED 3h SC RM CORRIDOR

**Item number** EN10080012  
**GTIN** 4015120080012



### Product description

- Single-battery 3-h emergency light for Recessed ceiling mounting. Optionally, operation in continuous or stand-by mode possible
- Downwards light emission and optimised for illumination of corridors. Test results indicated by coloured LEDs (green/red)
- Self-monitoring and optional controllable remote shutdown, as well as Status readout function via DALI bus



### Technical data

GENERAL	
Device category	Safety light
User interface	DALI-Bus
Remote controllable	–
Conformity	CE, RoHS, WEEE
Warranty	5 years
ATTACHMENT	
Installation type	Recessed mounting
Installation position	Ceiling
Installation dimension	Installation depth: 45 mm, Ø 43 mm
Type of connection	Push terminal
Connectable wire cross section	1,50 - 2,50 mm <sup>2</sup>
HOUSING	
Dimensions	Height/Depth 45 mm, Ø 55 mm
Weight	432 g
Material	UV-stabilised polycarbonate
Protection type	IP20
Permissible ambient temperature	5 °C...+35 °C
Relative humidity	5 - 95 %, non-condensing

Colour	white, similar to RAL 9016
ELECTRICAL VERSION	
Protection class	II
Nominal voltage	230 V / 50 Hz
In-rush current	1,3 A / 505 µs
Leakage current	0,019 mA
LIGHT	
Light emission	direct
Rated output	4 W
Luminous Flux (light)	155 lm
Luminous efficacy	38 lm/W
Colour temperature	approx. 4500 K
Colour rendering index Ra	> 75
Energy efficiency class	A++ to A
EMERGENCY LIGHTING	
Light duration	3 h
Power supply system	Decentralised (single-battery)
Battery status indicator	by LED
Automatic testing	✓

### Accessories


Product designation	Item number	GTIN
ELH FM BATTERY 2000mAh	EN00007361	4015120007361

# DATA SHEET


## ELH EL LED 3h SC RM CORRIDOR

**Item number**      **GTIN**  
EN10080012      4015120080012

### Scale drawing



### Light distribution



### Circuit diagram

