


Suno™ ROTARY DIMMER 300W ALL CHARGES Cat. No(s): 7 21X 79



1. USE

Rotary dimming for all types of lamps.

Can be associated with one or several push buttons, for ON/OFF or dimming control.

Integrates memory level function: the light switches ON the same level it has been switched OFF.

Soft-start and soft-stop lighting (2 s).


Mechanisms to be equipped with plates.

Screw or claw mounting.

2. RANGE


Description	White	lvory	Aluminium	Black
ROTARY DIMMER 300W ALL CHARGES	7 211 79	7 212 79	7 213 79	7 214 79

3. DISMANTLING



4. DIMENSIONS (mm)

7 21X 79



72,9

72,9

54,4


23,1

5. CONNECTION


4 terminals with screws Terminal capacity: 2 x 2.5 mm2 Stripping length: 8 mm

6. INSTALLATION

Simple



With push buttons



6. TECHNICAL CHARACTERISTICS

■ 6.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 40 Protection against impact: IK 04

■ 6.2 Material characteristics

Polygloss appearance

Colour: - White RAL 9003

- Ivory RAL 1013 - Aluminium

- Black

Material: - Front cover: ABS

- Halogen-free

- UV-resistant

Material of the support: - Metal - Halogen-free

Self-extinguishing:

850°C/30 s for insulating components holding live parts in place 650°C/30 s for other insulating components.


■ 6.3 Electrical characteristics

Voltage: 100 to 240 V~ Frequency: 50-60 Hz Standby consumption: 0.2 W

■ Load table

	R		L		C/L			
	(1)		(+		Dimmable	Dimmable LED
			•		9/\$/ <u>1</u>			
	-\$-						•	
200-240V~ 50 / 60 Hz	5 3	00 W	5 300 VA		5 300 VA		5 75 W <= 10 x	
100-200V~ 50 / 60 Hz	5 150 W		5 150 VA		5 150 VA		5 37 W <= 10 x	

■ Setting C or L



■ 6.4 Climate characteristics

Usage temperature: -5°C to $+35^{\circ}\text{C}$ Storage temperature: -10°C to $+70^{\circ}\text{C}$

7. MAINTENANCE

Surface cleaning with a cloth.

Do not use:

Aacetone, tar remover, trichloroethylene.

Maintenance with the following products:

Hexane (EN 60669-1), Methylated spirit, Soapy water, Diluted ammonia, Bleach diluted to 10%, Window-cleaning products, Pre-Impregnatedwipes.

Caution: Always test before using other special cleaning products.

8. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards. See e. catalogue.