Molybdenum bisulfide Grease MOS2 1 Lt (G016)

This Ambro-Sol lubricant is in a 1kg jar, and it has high features, in particular it's waterproof and it prevents oxidation, humidity and corrosion. This product is suitable for professional uses, but also at home.

Quantity	900 g
Barcode	EAN 13: 8034108892627
Box / Case	8 pz

MOLYBDENUM BISULFIDE GREASE – This superior classic black grease stands out because of its adhesiveness to metals in the most difficult conditions. It is high temperature resistant (300°C/572°F). It features extraordinary mechanical stability and provides excellent protection against oxidation, humidity and corrosion. It is ideal for lubricating both standard and high-load bearings.

Technical Specifications:

Aspect	Metal Jar
Color	Black
Odour	Odourless
Relative density	at 20°C 0,88 ÷ 0,92 g/ml
Flash point	>200° C
Solubility	Insoluble in water
Consistence	NLGI EP 2
Wheel Bearing test	(3 hours a 80°C) < 10 %
Penetration at 25°C 0.1 mm	265 - 295 mm/10
Drip point	> 270°C
Application temperature	-20°C - 300°C (peak)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.
After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT

Ambro-Sol - 25020 Cigole (BS) Italy - www.ambro-sol.com - info@ambro-sol.com

Ambro-Sol is a registered trademark – All rights reserved – Total or partial reproduction is prohibited.