



## Graphite Grease 400 ml (G019)

Graphite is a mineral, a good electric driver and has a high fusion temperature. This spray is a lubricant grease, perfect for maintenance and release of machinery and heavy equipment.



**HOW TO USE:** shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

Quantity	400 ml
Barcode	EAN 13: 8034108893662
Box / Case	12 pz

**GRAPHITE GREASE** – A special grease mixed with special substances that enhance the multi-functionality of this product. It has exceptional adhesion properties, it is water resistance, anti-corrosive, and anti-wearing. This lubricant can withstand the toughest conditions. It is suitable for ground moving/heavy equipment, agricultural, construction, and heavy industrial to lubricate joints, pins, bushings, guides, sliding surfaces, bearings, etc. Resistant to high temperatures (400°C/752°F).

### Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Graphite Black
Odour	Characteristic of solvent
Relative density	at 20°C 0,66 ÷ 0,70 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Consistency	NLGI EP2
Penetration	265-295 at 25°C 0.1 mm
Drip point	+ 180 °C
Application temperature	-40°C - +400°C (peak)

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

**BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT**