

## Time and light control

### Hour counters, Front panel, Analogue



taxxo 112



taxxo 612



UWZ52A

#### Description

- Hour counter with synchronous motor drive
- Front panel/wall installation devices with click-in or stretch clamp supports for walls up to a maximum of 10 mm thick
- Clamp or flat plug connection 6.3 mm
- Versions for direct voltage with quartz-controlled stepper motor
- Progress display

#### Product selection

Installation type	Farbe	Operating voltage	Type	Article number
Front panel installation, 45,2 x 45,2 mm	Black	110-127 V, 60 Hz	taxxo 112	05.15.1031.1
	Grey	220-240 V, 60 Hz	taxxo 112	05.15.1123.1
	Grey	18-46 V, 50 Hz	taxxo 112	05.15.1125.1
	Grey	220-240 V, 50 Hz	taxxo 112	05.15.1127.1
	Grey	220-240 V, 60 Hz	taxxo 112	05.15.1135.1
	Black	220-240 V, 50 Hz	taxxo 112	05.15.1142.1
	Black	220-240 V, 60 Hz	taxxo 112	05.15.1143.1
Front panel installation, 33 x 22 mm	Black	220-240 V, 50 Hz	taxxo 612	05.20.0006.1
Front panel installation, 50,2 x 25,2 mm	Grey	220-240 V, 50 Hz	taxxo 712	05.20.0004.1
Front panel installation, Ø 50,2 mm	Grey	220-240 V, 50 Hz	UWZ52A	05.15.10961
Wall installation, 48x48 mm	Grey	220-240 V, 50 Hz	taxxo 100	05.15.10011

#### Technical data

	taxxo 112 - 05.15.1031.1	taxxo 112 - 05.15.1123.1	taxxo 112 - 05.15.1125.1	taxxo 112 - 05.15.1127.1	taxxo 112 - 05.15.1135.1	taxxo 112 - 05.15.1142.1	taxxo 112 - 05.15.1143.1	taxxo 612	taxxo 712	UWZ52A	taxxo 100
Operating voltage	110-127	220-240 V	18-46 V	220-240 V			220-240 V				
Frequency	60 Hz		50 Hz	60 Hz	50 Hz	60 Hz	50 Hz				
Installation type	Front panel installation										Wall installation
Size	48 x 48 mm							36 x 24 mm	54 x 29 mm	Ø 58 mm	48 x 48 mm
Counting range	99 999,9 hours without reset										
Type of protection	IP 20										
Protection class	II according to EN 60 335-1										
Ambient temperature	-20°C ... 70°C										

# Time and light control

## Hour counters, DIN rail, Analogue

### Description



- Hour counter with synchronous motor drive
- Built in distributor device with quick fastening for 35 mm profile rails (DIN EN 60 715)
- Top mounting with additional terminal box cover plate, sealable
- Control panel installation with assembly kit possible
- Contact protection to comply with accident prevention regulation BGV A3
- Captive screw terminals

### Product selection

Installation type	Operating voltage	Type	Article number
DIN rail	110-120 V, 50 Hz	taxxo 403	05.21.0002.1
	330-380 V, 50 Hz	taxxo 403	05.21.0006.1
	220-240 V, 50 Hz	taxxo 403	05.21.0001.1
	220-240 V, 60 Hz	taxxo 403	05.21.0005.1

### Technical data

	taxxo 403 - 05.21.0002.1	taxxo 403 - 05.21.0006.1	taxxo 403 - 05.21.0001.1	taxxo 403 - 05.21.0005.1
Operating voltage	110-120 V AC	330-380 V AC	220-240 V AC	
Frequency	50 Hz			60 Hz
Width	2 modules			
Installation type	DIN rail			
Size front plate	35 x 45 mm			
Counting range	99 999,9 hours without reset			
Type of protection	IP 20			
Protection class	II according to EN 60 335-1			
Ambient temperature	-10°C ... 70°C			