


CDS-A/T

Item number

RK39500010040

GTIN

4015120010040



Product description

- Surface-mounted twilight switch for automatic lighting control
- In-built day time switch with various control options
- Floating relay contact
- The light value can be set on the outside of the housing

Technical data

GENERAL

Device category	Twilight switch
Special product features	In-built day time switch
User interface	Adjusting controller
Remote controllable	–
Conformity	CE, RoHS, WEEE
Warranty	3-year

ATTACHMENT

Installation type	Surface mounting
Installation position	Wall
Type of connection	Push terminal
Connectable wire cross section	1,50 - 2,50 mm ²

HOUSING

Dimensions	Length 114 mm x Width 80 mm x Height/ Depth 51 mm
Weight	264 g
Material	UV-stabilised polycarbonate
Protection type	IP54

Permissible ambient temperature	-25 °C...+55 °C
Relative humidity	5 - 95 %, non-condensing
Colour	white, similar to RAL 9010

ELECTRICAL VERSION

Protection class	II
Nominal voltage	230 V / 50 Hz
Power consumption	1,2 W

SENSORS

Light measurement	mixed light
-------------------	-------------

CONTROL


Channel 1	Lighting
Interface	Switching
Contact	make contact/floating
Switching capacity channel 1	230 V/50 Hz 2300 W/10 A (cos phi = 1) 690 VA/3 A (cos phi = 0,5) 12/24 V =/5 A, potenzialfreier Relaiskontakt 350 W LED

DATA SHEET

CDS-A/T

Item number **GTIN**
RK39500010040 4015120010040

Scale drawing



Circuit diagram

