


128, av. du Maréchal-de-Lattre-de-Tassigny - 87045 LIMOGES Cedex Tel: +33(0)5 55 06 87 87 Fax: +33(0)5 55 06 88 88 www.legrand.com

# MyHOME<sup>®</sup> Play Weatherproof radio multifunction switch



# 1. USE

Controls a circuit connected to its terminals or provides a volt-free contact (e.g.: for gate electronic control).


3 different operating modes: timer, switch, remote control switch. Its receiver function allows it to be controlled by 1-gang or 2-gang radio control units (transmitters), 4-scenario controls, IR detectors, remote controls.

Phase/neutral power supply.

### 2. RANGE

	Description	Colour	Cat. No.
0	Weatherproof radio multifunction switch	Grey	0 883 39

#### **3. DIMENSIONS**



Cat. Nos.	A	В	с	D
0 883 39	115	115	58	44

# 4. CONNECTION

Terminal type: screw Terminal capacity: 2 x 2.5 mm<sup>2</sup> max. Stripping length: 8 mm Tool to use: 4 mm flat screwdriver

### **5. TECHNICAL CHARACTERISTICS**

### 5.1 Mechanical characteristics

Protection against impacts: IK 02 Protection against solid bodies/liquids: IP 55 for assembled product

### 5.2 Materials

Halogen-free
UV resistant
Casing:

Polypropylene

Cover:

Polystyrene and elastomer

Mechanism protective cover:

ABS

Self-extinguishing:

+850°C/30 s for insulating parts holding live parts in place
+650°C/30 s for other parts made of insulating materials

#### 5.3 Electrical characteristics

Power supply: 100/240 V~ - 50/60 Hz 2.4 GHz radio technology

- Terminals:
- 1 Phase 1 Neutral
- 1 Common
- 1 Normally
- 1 Normally Closed contact 1 Normally Open contact
- Consumption during use: 14 mA/3.22 W

Consumption on standby: 8.4 mA/1.932 W

#### 5.4 Climatic characteristics

Operating temperature:  $0^{\circ}$ C to  $+45^{\circ}$ C Storage temperature:  $-20^{\circ}$ C to  $+65^{\circ}$ C

### 6. CARE

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Resistant to the following products: Hexane (EN 60669-1), methylated spirit, soapy water, diluted ammonia, bleach diluted to 10%, window-cleaning products, pre-impregnated wipes.

Caution: Always test before using special cleaning products.

Created: 20/07/2015

# 7. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards. See e-catalogue.

÷